Engineered Polymer (EP) Branch Opposing-port Multi-port Tee

Submittal Information
Revision B: Oct. 10, 2013

Project Information

Job Name:

Location: | Part No. Ordered:

Engineer: | Date Submitted:

Contractor: | Submitted By:

Manufacturer's Representative: | Approved By:

Technical Data

Material:	UDEL GF120
Maximum Temperature (no pressure):	320°F (160°C)
Maximum Working Temperature/Pressure:	210°F (99°C) at 150 psi
Maximum Multi-port Tee Flow for ¾" Inlet:	13.2 gpm at 12 fps 8.8 gpm at 8 fps

Product Information and Application Use

Engineered Polymer (EP) Branch Opposing-port Multi-port Tee features a ¾" ProPEX® inlet with opposing ½" ProPEX branch outlets.[1] These are designed for central location to facilitate piping in two directions. The tee is made of EP, which is proven in demanding hot-water applications.

✓ Description	Part Number	Length	Height	Width	Weight
☐ ¾" EP Branch Opposing-port Multi-port Tee, 3 outlets	Q2337550	3.58"	2.38"	1.18"	0.066 lbs.
☐ ¾" EP Branch Opposing-port Multi-port Tee, 4 outlets	Q2347550	3.58"	2.38"	1.18"	0.071 lbs.
☐ ¾" EP Branch Opposing-port Multi-port Tee, 8 outlets	Q2387550	6.08"	2.38"	1.18"	0.135 lbs.

Installation

Use any product designed to mount 1" copper pipe as a mounting bracket. For more information, refer to the Uponor AquaPEX® Professional Plumbing Installation Guide.

Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; ICC ESR 1099; IAPMO 3946

Related Applications

PEX-a Plumbing Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
www.uponorpro.com

Uponor Ltd.
2000 Argentia Road, Plaza 1, Suite 200
Mississauga, ON L5N 1W1 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
www.uponorpro.com

[1] ProPEX® is a registered trademark of Uponor, Inc. ProPEX ™ is a trademark of Uponor Ltd.