ProPEX® 1" Type L Valveless Copper Manifold

Submittal Information
Revision A: Jan. 9, 2009

Project Information

Job Name:

Location: | Part No. Ordered:

Engineer: | Date Submitted:

Contractor: | Submitted By:

Manufacturer's Representative: | Approved By:

Technical Data

Material:	Type L Copper
Maximum Temperature (no pressure):	320°F (160°C)
Maximum Working Temperature/Pressure:	210°F (99°C) at 150 psi
Maximum Flow Rate:	21 gpm

Product Information and Application Use

The ProPEX® 1" Copper Manifold is 6 feet in length and features 24 individual ½" ProPEX outlets spaced three inches on center.[1] The manifold is suitable for cutting to any length necessary to achieve the desired number of outlets. ProPEX Tool is required. ProPEX Rings sold separately.

✓	Description	Part Number	Height	Width	Length	Weight
☐	ProPEX 1" Type L Valveless Copper Manifold (1" x 6' with $^1/_2$" ProPEX, 24 outlets)	Q2512450	2.75"	3.00"	72"	8.70 lbs.

Installation

Any product designed to mount 1" copper pipe may be used as a mounting bracket. Any bend within 6 inches of the ProPEX connection to the manifold requires the use of a Tube Talon (F7050750) or Bend Support (A5110500 and A5150500). Refer to the AquaPEX® Professional Plumbing Installation Handbook or the Uponor Radiant Installation Handbook for additional information.

Standards

CAN/CSA B137.5; ASTM F877

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

IAPMO; ANSI/NSF 14- and 61-certified

Related Applications

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

[1]ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.