

Domestic Hot Water Recirculation Sensor, 10k

Submittal Information Revision A: July 10, 2008

Project Information					
Job Name:					
Location:	Part No. Ordered:				
Engineer:	Date Submitted:				
Contractor:	Submitted By:				
Manufacturer's Representative:	Approved By:				

Technical Data

Control: Measures the slab temperature

Type: 10K thermistor

Ambient Conditions: 32°F to 105°F (0°C to 41°C)

10% to 90% humidity non-condensing

Connections: RJ45 Cat5e connection

Product Information and Application Use

The Climate Cŏntrol™ Network System uses a variety of sensors to provide feedback and information to the main controls. The Network System supports domestic hot water (DHW) recirculation if there is only one DHW tank in use. When the DHW schedule is on, the recirculation pump runs continuously.



\checkmark	Description	Part Number	Height	Width	Depth	Weight
	Domestic Hot Water Recirculation Sensor, 10k	A9012003	1.50"	3.00"	2.50"	0.25 lbs.

Installation

The Domestic Hot Water Recirculation Sensor connects to the system with an RJ45 Cat5e patch cable, using less wire than conventional control systems. Refer to the Climate Control Network System Manual for additional information.

Standards

Class II wiring

Codes

N/A

Listings

N/A

Related Applications

Radiant Heating and Cooling System Snow and Ice Melting System Permafrost Protection System Turf Conditioning System

Contact Information

Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Fas: (952) 891-2008 www.uponor-usa.com Uponor Ltd. 655 Park Street Regina, SK S4N 5N1 CANADA Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca