Uponor AquaPEX® Red, Straight Length

Submittal Information
Revision A: July 23, 2009

Project Information

Job Name:

Location: | Part No. Ordered:

Engineer: | Date Submitted:

Contractor: | Submitted By:

Manufacturer's Representative: | Approved By:

Technical Data

Material:	Crosslinked polyethylene PEX-a Engel Method; PEX 5006
Standard Grade Hydrostatic Ratings (PPI):	200°F (93°C) at 80 psi 180°F (82°C) at 100 psi 73.4°F (23°C) at 160 psi
Linear Expansion Rate:	1.10"/10°F (12°C)/100'

Product Information and Application Use

Uponor AquaPEX® Red tubing is used for hot and cold domestic potable water distribution and radiant heating systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing.

✓	Description	Part Number	I.D.	O.D.	Weight
☐	½" Uponor AquaPEX Red, 20-ft. straight length, 500 ft.	F2930500	0.475"	0.625"	28.0 lbs.
☐	¾" Uponor AquaPEX Red, 20-ft. straight length, 300 ft.	F2930750	0.671"	0.875"	31.0 lbs.
☐	1" Uponor AquaPEX Red, 20-ft. straight length, 200 ft.	F2921000	0.862"	1.125"	35.0 lbs.

Installation

Approved fittings systems are ProPEX® and APR.[1] Refer to the AquaPEX Professional Plumbing Installation Handbook for additional information.

Standards

CSA B137.5; ASTM F876; ASTM F877; ASTM F1960; ASTM-E84; ASTM-E119/UL 263

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

HUD; WARNOCK HERSEY; NSF; cNSFus certified; ITS; UL;; ANSI/NSF 14- and 61-certified; CAN/ULC S102.2; U.S.: ¾" diameter and smaller; Canada: 1" diameter and smaller

Related Applications

PEX-a Plumbing Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca

[1]ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.