High-density Polyethylene (HDPE) Flange Adapter

Submittal Information Revision A: Nov. 18, 2009

Manufacturer's Representative:

uponor

Project Information

Job Name:

Location:Part No. Ordered:Engineer:Date Submitted:Contractor:Submitted By:

Technical Data

Material: 3408 Polyethylene material

Standard Grade Hydrostatic Ratings: 140°F at 80 psi (60°C at 5.5 bar)

120°F at 100 psi (49°C at 6.9 bar)

100°F at 125 psi (38°C at 8.6 bar)

73.4°F at 160 psi (23°C at 11 bar)

Maximum Recommended Flow Rates: 2" — 41 gpm; 3" — 116 gpm; 4" — 226 gpm

Product Information and Application Use

Use Uponor's high-density polyethylene (HDPE) Flange Adapter to convert 2", 3" and 4" HDPE tubing to non-ferrous metal pipe. HDPE fittings are designed for heating applications that contain no ferrous corrodible components or where ferrous components are isolated from the tubing.



✓	Description	Part Number	ID	OD	Length	Width	Height	Weight
2"	HDPE Flange Adapter	B2182000	1.943"	2.375"	4.0"	4.0"	6.0"	0.50 lbs.
3"	HDPE Flange Adapter	B2183000	2.864"	3.500"	5.0"	6.0"	5.0"	0.95 lbs.
4"	HDPE Flange Adapter	B2184000	3.682"	4.500"	6.0"	6.0"	6.0"	1.45 lbs.

Installation

Connect tubing and fittings through fusion welding. For additional information, refer to the Radiant Floor Heating Installation Handbook.

Standards

ASTM D3350; CSA B137.1; CGSB 41-GP-25M; NSF 14; NSF 61

Codes

NSPC; NPC of Canada

Listings

PPI PE-3408; NSF 14- and 61-certified

Related Applications

Radiant Heating and Cooling Systems Snow and Ice Melting Systems Permafrost Protection Systems Turf Conditioning Systems

Contact Information

Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: (800) 321-4739 Fax: (952) 891-2008 www.uponor-usa.com Uponor Ltd.

2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA

Phone: (888) 994-7726 Fax: (800) 638-9517 www.uponor.ca